

User informaion

Cut retardant garments – PROFESIONAL CZ

Item numbers of cut retardant products: 022161, 02271, 022172

Item numbers of complementary products: 022199 and 022170

For maximum protection, comfort and safety when using this product is absolutely necessary to ensure the following information:

WARNING:

Safety clothing can not provide absolute protection against injuries by chainsaws. Level of protection depends on numerous factors su as speed and torque, severity and duration of contact with the tool, angle at which the bar contacts the fabric, working position etc.

This protective clothing is not a substitute for safe working

techniques. Improper use of chainsaws can lead to accidents.

Therefore it is necessary to follow the approved processes and ensure compliance with applicable safety regulations and warnings in

the chainsaw user instructions. Safety clothing requires special and regular cleaning. Heavily soiled clothes should be washed

immediately after use. Remnants of resins, oils and fuels can have a

detrimental effect on the function of safety clothing. Usual laundry detergent are recommended for washing. To maintain the protective

functions should be wet clothes straighten and stretch to the natural shape after washing and let dry freely. Higher than the permissible

temperature reduces the protective function and properties

(shrinkage). If possible avoid contact of this safety product with

pointed or sharp objects (chain saws, arbors, metal tools, etc.) and

contact with aggressive substances such as acids, oils, solvents,

fuels, animal faeces, in order to prevent material damage. It is also

necessary to avoid contact with hot objects and heat sources (open flames, stoves, etc.).

Clothing must be cleaned before further use as described above.

Choosing of the right size, the instructions for dressing and undressing:

Generally it is necessary to choose clothes, so that job performance is possible without any restrictions. Clothes should not be overly broad as to avoid any risk of chatch the part of clothes due to its redundant width. Dressing and undressing runs same as usual clothes.

Instructions for maintenance, control of the wearer:

60 ° C washing with limited mechanical action and the gradual cooling, no spinning. Do not tumble dry, iron temperature max. 110 ° C, limited chemical cleaning, do not bleach. User should check the condition of clothes mainly the saw protection in appropriate intervals.

Corrections:

Only the upper fabric can be fixed but chainsaw protective lining must not be sewn through. It is not possible to make any changes on chainsaw protective liner such as shortening of the legs, abridge nor quilt! Every amendment changes decreases, respectively destroy the chainsaw protective effect!

Reserve parts:

Upper fabric for repair, braces, fasteners, zippers are available on request from the manufacturer, if necessary.

Criteria for exclusion:

Safety clothing with damaged or altered safety liner must not be used! Parts of clothes that are damaged or modified from other causes, must be immediately excluded.

Basic materials:

Safety garments are made from - upper fabric (53% polyamid / 47% cotton), againstcut protection (85% polyester/ 30% polypropylene) and liner (100% cotton and 100% polyester).

Information about materials, which may cause allergic reactions:

Materials used in production are not source of harmful effects, respectively are not known.

Aging of garments:

Cut retardant apparel and materials are subject to a certain degree of aging. In professional logging, for example, the maximum period of usage is considered to be about 2 years. In non-professional use (occasional use) a period of usage of up to a maximum of 6 years is considered acceptable. However, the period of usage always depends on the specific application and load in each case, which can vary greatly. In case of doubt, the product should be examined to ensure it conforms to current technical requirements, and also for wear or charges and replaced with a new product if necessary.

Weight:

Informative product weight of size 52/182 cm height

022161/52/182 - approx. 2,020 kg

022171/52/182 - approx. 1,400 kg

022172/52/182 - approx. 1,210 kg

022199/52/182 - approx. 1,320 kg

022170/52/182 - approx. 0.610 kg

Testing standards and legislation:

This cut retardant products complies with EU Directive 89/686/EEC

Products with pictograms for cut retardant protection meet the requirements of EN 381, Part 5, Design A, Class 1 (20 m / s) - scope of the protection across the entire on front of leg and additional plus 50 mm on the left side of the outer leg (side seam) and on the inside (step seam) of right leg (seen from the perspective of wearer).

Protection of low part of abdomen almost 20 cm up from a step seam with 3cm gap in the middle.

Storage, maintenance and use restrictions:

Safety garments are packed in protective plastic bag. Store products in a dry and well-ventilated places and avoid extreme temperatures, contact with liquids or UV radiation (for ex. shop windows). Use limitations may arise due to composition of matter, such as manipulation with fire.

For further information please contact:

Company: Profesional CZ s.r.o.

Address: Bořich 5, 326 00 Plzen

Tel.: +420 377 244 782

Fax: +420 377 242 626

E-mail: info@profesional-plzen.cz

www.profesional-plzen.cz

Number of certificate of type test - and authorized notified body:

07 0009 T/NB - AO nr.224 - NO nr.1023